

Airlift 2 Instructions

- 1** Lay the Airlift flat on the ground inside facing down. Locate the metal O-Ring and two plastic D-rings. Next, locate the carabiner attached to one end of the daisy-chain strap and clip it to the metal O-ring. Next, run the opposite end of the daisy-chain strap through the two plastic D-rings (D-rings act as guides to keep the strap in place).
- 2** Do the same with the second daisy chain strap, locate the other metal O-ring clip into it and run the opposite end of the daisy-chain strap through the plastic D-ring. Then turn the Airlift over so the inside is facing up.
- 3** Refer to the instructions on the stuff-sack in preparation of lifting the dog.
- 4** Once the dog is situated in the Airlift and is ready to be lifted, the person assisting should place their hands through the hand-loops on the daisy-chain straps closest to the person carrying the dog. When ready assist in lifting the dog by lifting up using the hand-loops.
- 5** Depending on type of terrain-uphill (see Image) or downhill (see image) you can utilize the sewn loops on the shoulder straps (two sets front facing and rear facing) of the Airlift for uphill or downhill or on flatter terrain keep the straps in the O-Rings to assist in carrying the dog.
- 6** Assist getting up hills by clipping the front side or back side pre-sewn loops on the Airlift shoulder pads.
- 7** Assist in balance and speed control by clipping the rear facing pre-sewn loops on Airlift shoulder pads.

